

# LiftMaster® 2016 UL 325 LISTED GATE OPERATOR FEATURE CHART



## RESIDENTIAL GATE OPERATORS

Model Number	LA500PKGU	LA400PKGU	LA412PKGU	RSL12U	RSW12U
<b>Description</b>	24VDC Residential/ Light Commercial Linear Actuator	24VDC Residential Linear Actuator	12VDC Solar Residential Linear Actuator	12VDC Residential/ Light Commercial Slide Gate Operator	12VDC Residential Swing Gate Operator
<b>Battery Backup</b> Powers up when the power's down	500 cycles	400 cycles	Solar	114 cycles	147 cycles
<b>Security+ 2.0® 3 Channel Receiver</b> Virtually eliminates interference and extends range	Yes	Yes	Yes	Yes	Yes
UP TO 50 REMOTE CONTROL CAPACITY FOR ALL GATE OPERATORS					
<b>MyQ®</b> Controls your gate from anywhere with your smartphone	Yes	Yes	Yes	Yes	Yes
<b>P3 Motor®</b> Meets the exact requirements needed to move your gate	Yes	Yes	Yes	Yes	Yes
<b>Monitored Safety Inputs (Color Coded)</b>	6 Inputs (Main and Expansion Board)	3 Inputs (Main Board)	3 Inputs (Main Board)	3 Inputs (Main Board)	3 Inputs (Main Board)
<b>Exceptional Standby Power</b>	Up to 24 days	Up to 97 days	Up to 126 days	Up to 63 days	Up to 63 days
<b>Best-in-Class Solar Performance*</b>	Approx. 43 cycles per day	Approx. 81 cycles per day	Approx. 100 cycles per day	Approx. 33 cycles per day	Approx. 41 cycles per day
<b>DC Motor with Soft Start/Stop</b>	Yes	Yes	Yes	Yes	Yes
<b>Diagnostic Code Display-2 Digit LED</b>	Yes	Yes	Yes	Yes	Yes
<b>Wireless Dual-Gate Operation</b>	Yes	Yes	Yes	Yes	Yes
<b>PosiLock® Feature</b>	-	-	-	Yes	-
<b>Fire Department Compliant</b>	Yes	Yes	Yes	Yes	Yes
<b>Electronic Limits</b>	Yes	Yes	Yes	Yes	Yes
<b>Expansion Board Included (2) Aux Relays, Quick Close/Anti-Tailgate</b>	Yes	Optional	Optional	Optional	Optional
<b>Plug-in Loop Detector Inputs (LOOPDETLM)</b>	Yes	With Optional Expansion Board	With Optional Expansion Board	With Optional Expansion Board	With Optional Expansion Board
<b>Pre-Motion Warning Alarm</b>	Yes	With Optional Expansion Board	With Optional Expansion Board	With Optional Expansion Board	With Optional Expansion Board
<b>Dual Voltage</b>	120/230V Single Phase	-	-	-	-
<b>Warranty Period</b>	2 years	2 years	2 years	3 years	3 years
<b>Max. Gate Length</b>	18 ft.	16 ft.	16 ft.	25 ft.	16 ft.
<b>Max. Gate Weight</b>	1600 lbs.	850 lbs.	850 lbs.	800 lbs.	1000 lbs.
<b>Recommended Cycles</b>	300 cycles per day	100 cycles per day	100 cycles per day (see solar chart for specific details)	120 cycles per day	250 cycles per day



4261 S Country Club - Tucson, AZ 85714  
1.520.320.1810 - 1.800.509.2140  
sales@antech.com www.antech.com ROC 168402

For more information about our best-in-class features, see specific product sell sheets at [LiftMaster.com](http://LiftMaster.com)

\*Cycles noted are for Zone 1 (6 hours sunlight per day).

# LiftMaster® 2016 UL 325 LISTED GATE OPERATOR FEATURE CHART



## ELITE® SERIES DC COMMERCIAL GATE OPERATORS

## ELITE® SERIES AC COMMERCIAL/INDUSTRIAL GATE OPERATORS

Model Number	CSW24U	CSL24U	HCTDCU	CSW200	SL3000	SL585	SL595
Description	24VDC High-Traffic Commercial Swing Gate Operator	24VDC High-Traffic Commercial Slide Gate Operator	24VDC High-Traffic Overhead Door and Gate Operator	AC Commercial High-Traffic Swing Gate Operator	AC Commercial High-Traffic Slide Gate Operator	AC Industrial Slide Gate Operator	AC Heavy-Duty Industrial Slide Gate Operator
<b>Battery Backup</b> Powers up when the power's down	146 cycles	208 cycles	112 cycles	-	-	-	-
<b>Security+ 2.0®</b> <b>3 Channel Receiver</b> Virtually eliminates interference and extends range	Yes	Yes	Yes	Yes	Yes	Yes	Yes
	UP TO 50 REMOTE CONTROL CAPACITY FOR ALL GATE OPERATORS						
<b>MyQ®</b> Controls your gate from anywhere with your smartphone	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>P3 Motor®</b> Meets the exact requirements needed to move your gate	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>Monitored Safety Inputs (Color Coded)</b>	6 Inputs (Main and Expansion Board)	6 Inputs (Main and Expansion Board)	6 Inputs (Main and Expansion Board)	6 Inputs (Main and Expansion Board)	6 Inputs (Main and Expansion Board)	6 Inputs (Main and Expansion Board)	6 Inputs (Main and Expansion Board)
<b>Exceptional Standby Power</b>	Up to 24 days	Up to 24 days	Up to 72 days	-	-	-	-
<b>Best-in-Class Solar Performance*</b>	Approx. 16 cycles per day	Approx. 22 cycles per day	-	-	-	-	-
<b>DC Motor with Soft Start/Stop</b>	Yes	Yes	Yes	-	-	-	-
<b>Diagnostic Code Display-2 Digit LED</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>Wireless Dual-Gate Operation</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>PosiLock® Feature</b>	-	Yes	Yes	-	-	-	-
<b>Fire Department Compliant</b>	Yes	Yes	Yes	-	With Optional Firebox	-	-
<b>Electronic or Mechanical Limits with Automatic Force</b>	Electronic	Electronic	Electronic	Mechanical	Mechanical	Mechanical	Mechanical
<b>Expansion Board Included (2) Aux Relays, Quick Close/ Anti-Tailgate</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>Plug-in Loop Detector Inputs (LOOPDETLM)</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>Pre-Motion Warning Alarm</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>Dual Voltage</b>	120/230V Single Phase	120/230V Single Phase	120/230V Single Phase	-	-	Selectable within Phase	Selectable within Phase
<b>Warranty Period</b>	7 years Res. 5 years Comm.	7 years Res. 5 years Comm.	7 years Res. 5 years Comm.	7 years Res. 5 years Comm.	7 years Res. 5 years Comm.	2 years	2 years
<b>Max. Gate Length</b>	18 ft.	50 ft.	12 ft. Door/Gate	1/2 HP 18 ft. 1 HP 22 ft.	1/2 HP 37 ft. 1 HP 37 ft.	1/2 HP 45 ft. 1 HP 70 ft. 1 1/2 HP 75 ft.	1 HP 70 ft. 1 1/2 HP 80 ft. 2 HP 90 ft.
<b>Max. Gate Weight</b>	1600 lbs.	1500 lbs.	800 lbs.	1/2 HP 1600 lbs. 1 HP 2000 lbs.	1/2 HP 1000 lbs. 1 HP 2000 lbs.	1/2 HP 1000 lbs. 1 HP 1600 lbs. 1 1/2 HP 1900 lbs.	1 HP 1700 lbs. 1 1/2 HP 2100 lbs. 2 HP 2500 lbs.
<b>Recommended Cycles</b>	High-Cycle, High-Temperature Continuous Duty	High-Cycle, High-Temperature Continuous Duty	High-Cycle, High-Temperature Continuous Duty	High-Cycle, High-Temperature Continuous Duty	High-Cycle, High-Temperature Continuous Duty	20 cycles per hour	25 cycles per hour