



Built Smart, Attractive and Tough

LiftMaster® IPAC (Internet Protocol Access Control) is the first Internet-enabled outdoor access control system with Voice over Internet Protocol (VoIP). By harnessing the power of a high-speed connection, IPAC's innovative technology allows you to work smarter and more efficiently, and its contemporary design features a durable enclosure, which enhances your property's image.

Streamline your workload and reduce directory maintenance downtime.

- **Make updates 24/7** through an IP address (no software to install), so you never have to take IPAC offline.
- **Manage resident info** from any browser on your LAN, so you do not physically visit the unit.
- **Eliminate long-distance fees** and replace old analog phone lines with VoIP technology.
- **Never run out of system memory** with 50,000-resident capacity.

Give your community's image an upgrade for years to come.

- **Aircraft aluminum alloy front panel** is rust-, scratch- and dent-resistant.
- **Weathertight construction** (IP65 rated).
- **Withstands -20°F to 130°F**, providing year-round protection.
- **10" color touchscreen** is easy to use by your residents and guests.
- **Full on-screen keyboard** lets guests quickly find a resident's name without scrolling.
- **Reflective coating and auto dimming** allow easy readability in any light.
- **Durable protective screen** withstands constant use.



4261 S Country Club - Tucson, AZ 85714

1.520.320.1810 - 1.800.509.2140

sales@antech.com www.antech.com ROC 168402


Included Accessories:



Passport Receiver (PPWR)

Allows for simple block programming. Tri-band, narrow-band technology provides extended range.

Optional Accessories:




Paintable Faceplate and Shroud (IPACTRK)

Permits color customization. Metal shroud ensures screen visibility even in sunlight.



Retrofit Trim Ring (IPACRTR)

Makes installation easy when replacing both flush mount Infinity L and ICON 26 models.



HID ProxPoint® Plus Mini (SNARHIDPOINT)

Proximity reader provides multiple configuration options and is both sleek and inconspicuous.



Keypad (IPACKEY)

For Customers needing multiple keypad options, IPAC accommodates an external keypad.



Postal Lock Box (IPACPLB)

Meets postal requirements while offering flexibility for right- or left-side installation.



Camera Kit (IPACCAMK)

This high-performing camera is perfect for applications requiring visual installations.



Internet Protocol Door Controller (IPACIPDCC)

Power over Ethernet (PoE) solution for remotely managed multi-site applications. Compatible with Wiegand readers.

SPECIFICATIONS

HARDWARE SPECIFICATIONS

DIMENSIONS

- Height: 17.9"
- Width: 12.73"
- Depth: 3.74"

MATERIAL

Front Panel: T6061 Aircraft Aluminum Alloy
Enclosure: 13-Gauge Cold-Rolled Steel

FINISH

Front Panel: Silver Hard Anodized Coat
Enclosure: Light Gray Powder Coat

ENCLOSURE COMPONENTS

- Microphone
- Speaker
- LED Lighted Recessed Faceplate
- Display
 - 10" Color Resistive Touchscreen
 - Dusk to Dawn Light Sensor
 - Heavy-Duty Piano Hinge
 - HID ProxPoint® Plus Mini Card Reader Provision (optional)
 - Touch Keypad Provision (optional)

SUPPLY VOLTAGE

16VDC, 2.5 Amps (Transformer Input 120VAC, 60Hz, 1.0 Amps)

OPERATING CURRENT

1.17 Amps (without accessories)
Surge Suppression—EFT: 2 KV Power Line, ESD: 15Kb Hbm/8KV Direct/200V Mm (compliance with UL)
Unit Operating Temperature Range: -20°F to 130°F

ENCLOSURE

Outdoor IP65 Rated
(2) Wiegand Inputs—26-, 30- and 34-bit ODD and 34-bit EVEN
12V, 250mA Power Output (per port)
(4) Relay Outputs—Single Pole Double Throw, Maximum Voltage of 30VDC/AC and Output Current of 3 Amps

ACCESS CONTROL SPECIFICATIONS

24/7 Real-Time Data Access Management and Monitoring—Standard
Up to 50,000 Total Credentials—Standard
50,000 Transaction Event Buffer Non-Volatile—Standard
Up to 50,000 Phone Numbers
Email and Text Capability (selectable)
16 Group/Security Levels, 32 Holiday Schedules, 32 Time Schedules
Device Status Alerts

REQUIREMENTS

Hard-Wired High-Speed Internet Connection (10/100 Mbps)
- Up to 325 feet without Additional Networking Hardware
Active SIP (Session Initiation Protocol) Service

WARRANTY

2-Year Warranty (see manual for details)

INCLUDED ACCESSORY SPECIFICATIONS

Passport Receiver (PPWR)
- LiftMaster® Security+ 2.0™ Technology
- Supports Standard 26-, 30-, 31-, 34- and 50-bit Wiegand Protocol
- 12,000 Remote Capacity

OPTIONAL ACCESSORY SPECIFICATIONS

Paintable Faceplate and Shroud (IPACTRK)
- Material: Lexall Gray Prime Plastic
- 14-Gauge Black Powder-Coated Steel
Retrofit Trim Ring (IPACRTR)
- Fits: Infinity L and Icon 26 Flush Mount Openings
- Material: 16-Gauge Black Powder-Coated Steel
HID ProxPoint® Plus Mini (SNARHIDPOINT)
- Special Provisioning for LiftMaster IPAC
Keypad (IPACKEY)
- Material: T6061 Aircraft Aluminum Alloy
- Finish: Hard Anodized
- Interface: Piezo Touch Keys
Postal Lock Box (IPACPLB)
- Height: 7.65"
- Width: 5.65"
- Depth: 3"
- Panel Material: T6061 Aircraft Aluminum Alloy
- Panel Finish: Post-Office Blue Hard Anodized Enclosure
- Enclosure Material: 14-Gauge Light Gray Powder-Coated Steel
Internet Protocol Door Controller (IPACIPDC)
- Intended for use in indoor environments only
- Height: 4.5"
- Width: 3"
- Depth: 1.25"
- (2) Wiegand Inputs
- (2) Relay Outputs
Camera Kit (IPACCAMK)
- Camera and Transformer

Capabilities and Features	IPAC Panel
System Capacities	
Residents	50,000
Stored Events Buffer	50,000
Wiegand Inputs	Up to 2
Access Points—Gates or Doors	2 Programmable/2 Auxiliary
Panels per System	1
Groups per System	16
Holidays per System	32
Schedules per System	32
Cards per User	1
System Features	
Anti-Passback (Timed or True) Zones	2
Credential Types	Wiegand and PIN
Card and PIN Access (2-Factor Credentials)	Yes
Group-Enabled Schedules	Yes
Schedule Exceptions	No